



# Instantor®

Technical Specification  
Instantor Press System



Product	Instantor® Press System
Description	Instantor Press Fittings & Pex-Al-Pex Pipe
Size Range	Fittings - 16mm, 20mm, 26mm, 32mm Pipe – 16mm, 20mm, 26mm & 32mm x 4M Lengths 16mm x 100M, 20mm x 100M, 26mm x 50M, 16mm x 500M x Plain Coils 16mm x 100M, 20mm x 50M, 26mm x 25M, 32mm x 25M, 26mm x 50M Insulated Coils
Max Operating Pressure @ 95°C	6 bar
Max Operating Pressure @ 20°C	10 Bar
Max Operating Temperature	95°C
Minimum Operating Temperature	0°C
Max Peak Temperature (at 1 hour)	110°C
Material Specification	CW617N Brass body & 304 Stainless Steel sleeves
Conforms to standard	ISEN 21003-1 NSAI Licence No 1.153.001
WRAS Approval	Cert # 1707001 & # 1804354

Products produced from Brass are NOT suitable for use underground

**IE** T: 01 842 6255 E: sales@instantor.ie [www.instantor.ie](http://www.instantor.ie)

**UK** T: 0121 737 2515 E: sales@instantor.co.uk [www.instantor.co.uk](http://www.instantor.co.uk)

**Sanbra Fyffe Ltd - Instantor**

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

**Instantor UK**

1 Dagger Rd, Lisburn, Northern Ireland, BT28 2TJ

