



# Instantor®

**Manifolds PWK  
Technical Specification**



Product Code	771871PWK , 771872PWK , 771874PWK, 771875PWK, 771877PWK, 771878PWK, (Imperial Dimensions)
Description	Instantor Press adapters Manifolds Male X Female BSP ended with Swivel Press branches.
Size Range	¾" BSP (G3/4") X16mm" , 1" BSP (G1") x16mm – in 2 Port, 3 Port and 4 Port configurations.
Max Operating Pressure	10 Bar @ 20°C , 6 Bar @ 95°C
Min Operating Pressure	0 Bar
Max Operating Temperature	110°C (short overload of up to a Max. 1 Hour)
Min Operating Temperature	-5°C (Flowing Fluid)
Material Specification	Manifold -Copper Alloy : EN12165 CW617N DW Brass O-rings – EDPM Press Sleeve' – SS304.
Manufactured to:	ISO9001 ISO14001 ISO228 WRAS No. 1907328. & KIWA No. 1907745. ISO21003 series.

**BRASS SHOULD NEVER BE USED IN UNDERGROUND APPLICATIONS!!**

**IE** T: 01 842 6255 E: sales@instantor.ie [www.instantor.ie](http://www.instantor.ie)

**UK** T: 0121 737 2515 E: sales@instantor.co.uk [www.instantor.co.uk](http://www.instantor.co.uk)

**Sanbra Fyffe Ltd - Instantor**

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

**Instantor UK**

1 Dagger Rd, Lisburn, Northern Ireland, BT28 2TJ

