Manifolds + Iso's Technical Specification

Product Code	771892(K) , 771893(K) , 771894(K), 771895(K), 771910(K), 771911 (K) Add 'K' to end of code for Multilayer Nut and insert Adapters.
Description	Manifolds Male X Female BSP ended. With 1/2" compression branches or Add 'K' to end of code for Multilayer Adapters.
Size Range	¾" X ½" , 1" x ½" – in 2 Port, 3 Port and 4 Port configurations with Isolation valves
Max Operating Pressure	10 Bar
Min Operating Pressure	0 Bar
Max Operating Temperature	65°C (with occasional excursions to 95°C for 1Hr Max)
Min Operating Temperature	-20°C (Flowing Fluid)
Material Specification	Copper Alloy Brass O-ring – EDPM
Manufactured to:	ISO9001 ISO14001 EN:1254-2 ISO228 ISO21003

BRASS PRODUCTS SHOULD NEVER BE USED IN UNDERGROUND APPLICATIONS!

IE **T:** 01 842 6255 **E:** sales@instantor.ie **www.instantor.ie**

UK **T:** 0121 737 2515 **E:** sales@instantor.co.uk **www.instantor.co.uk**

Sanbra Fyffe Ltd - Instantor

Instantor Works, Santry Avenue, Santry, Dublin D09 K160

Instantor UK

1 Dagger Rd, Lisburn, Northern Ireland, BT28 2TJ